

**SMART UND SWISS SEIT 1876** 


C 50 AC1 – Two wheel battery sprayer

# For professionals from professionals: Powerful (battery) performance for demanding situations – with CAS power



## Two wheel battery sprayer – with CAS system Electronically pressure controlled, powerful, quiet and environmentally friendly...

The well-proven concept of controlling the pressure by electronics has been complemented by the cross-manufacturer battery pack system. The guick-change system of the CAS battery pack enables uninterrupted working. The electronic control allows to preset the pressure and keeps it at a constant level. The electronic also monitors important components such as the pump and battery pack. A constant pressure results in a constant spray pattern. This maximizes effectiveness while reducing the amount of solution used. Depending on the pressure and the accessories used, the battery pack lasts up to 22 hours. During this time, up to 163 gal can be applied. In addition, the C 50 is equipped with a switchable mixing function.



### Real work comfort

- Zero emission, quiet and environmentally friendly
- Robust wheels
- 32 ft hose, large application radius
- Quick-charger
- Quiver for inserting accessories
- Switchable mixing function

# One battery, many solutions | CAS|



- CAS\* Unlimited combinations
- Cross-manufacturer compatibility for over 300 devices
- Different battery packs obtainable (up to 10 Ah)
- Charge level is displayed by LED lights
- \* CAS (Cordless Alliance System is a cross-manufacturer battery pack system of leading power tool brands)

## **Unique Birchmeier features**

- Constant spray pattern
- · Large filling opening with strainer
- Top quality output assembly
- Robust pump
- Separate drainage opening
- A wide range of accessories



## **Electronically controlled**

- Intellegent pressure control
- Operating pressure adjustable (14 to 87 psi)
- Depending on the pressure and the accessories used, the battery pack lasts from 3 to 22 hours
- Energy efficient
- Protective setup for pump and battery pack

AS 1200 AC1

Art.No. 12129001

• Flow rate of up to 1.3 gal/min depending on nozzle configuration



**Further information** 















Art.No. 10501606 Art.No. 28502325-SB

## Spray period\* c 50 AC1



#### Spray period (hours)

## Spray output\* c 50 AC1



<sup>\*</sup> per battery pack charging

## **Technical Specifications C 50 AC1**

Tank volume	volume 13.2 gal	
Pressure range	14 – 87 psi	
Battery pack (with scope of delivery C 50 AC1)	18 V LiHD / 8.0 Ah	
Battery pack charging time	< 160 min	
Nozzle type	Adjustable nozzle 1.7 mm	
Nozzle material	Brass	
Flow rate (at 14 – 87 psi)	0.079 - 0.174 gal/min (Spraying)	
Gaskets	FKM	
Fitting assembly	Screw fitting	
Pump	Diaphragm pump 12 V DC	
Pump performance (0 bar)	1.585 gal/min max.	
Temperature (min./max.)	5 °C / 30 °C	
Dimensions (L x W x H)	1.57 x 1.88 x 3.28 ft	
Empty weight with battery pack	65 lbs	
Sound pressure level	< 70 dB (A)	

C 50 AC1 (with battery pack 8.0 Ah/charger)	Art.No. 12161801	
Battery pack 18 V Li-Power / 2.0 Ah	Art.No. 12070301	
Battery pack 18 V Li-Power / 4.0 Ah	Art.No. 12071401	
Battery pack 18 V Li-Power / 5.2 Ah	Art.No. 12072501	
Battery pack 18 V LiHD / 8.0 Ah	Art.No. 12073601	
Battery pack 18 V LiHD / 10.0 Ah	Art.No. 12100701	
Quick-charger ASC 55 (230 V)	Art.No. 12070101	

#### Nozzle performance

Pressure (psi)	Adjustable nozzle 1.7 mm (Sprühen) (gal/min)	Fanjet nozzle (TP 8002 MS) (gal/min)	Duro mist nozzle 1.65 mm (gal/min)	Herbicide Floodjet nozzle 1.6 mm (blue) (gal/min)		
7	0.058	0.121	0.158	0.285		
14	0.079	0.171	0.211	0.404		
29	0.108	0.208	0.290	0.567		
43	0.129	0.240	0.343	0.694		
58	0.147	0.256	0.396	0.800		
72	0.161	0.269	0.449	0.895		
87	0.174	0.295	0.475	0.980		

#### Birchmeier backpack sprayers








		_	
	<b>REB 15 AC1</b> Art.No. 12070801	<b>REC 15 AC1</b> Art.No. 12070901	<b>AS 1200 AC1</b> Art.No. 12129001
Tank volume	3.96 gal	3.96 gal	-
Pressure range	14 – 43 psi	7 – 87 psi	7 – 145 psi
Spray period per battery pack charging	4.3 h (at 21 psi)	12 h (at 21 psi)	25 min. at max. 6 h (Stufe 1 – 5)
Spray output per battery pack charging	24 gal (at 21 psi)	71 gal (at 21 psi)	165 gal (at 21 psi)
Stress class*	2	1	1

<sup>\* 1 =</sup> Very heavy duty 2 = Heavy duty 3 = Standard duty 4 = Light duty

#### Your Birchmeier distributor



## BIRCHMEIER°

US Distribution ITB Company, Inc. 800-866-1357 email: info@itbcompany.com www.birchmeier.us

Art.No. 12165718 | v0624